

# 2026 OUTLANDER 6X6 BACKCOUNTRY 1000R T



Stealth Black

## PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Selectable 4WD / 6WD with Visco-4Lok front differential
- pDrive primary CVT with work calibration and extra low gear
- Engine modes, Intelligent engine braking technology (iEB) and speed limiter
- 30 in. XPS Iron Force tires with 14 in. aluminum beadlock wheels
- SHOWA gas shocks
- Oversized 4-Discs braking system
- Full skid plate, front bumper, footwell protectors, A-arms protectors, handguards
- 3,500 lb winch with synthetic rope
- RF Digitally Encoded Security System (D.E.S.S.)
- Aluminum handlebar with riser
- 1,000 lb bed capacity
- 1,830 lb towing capacity
- LED headlights and tail lights, LED signature lights
- Special edition seat
- Mirrors
- Flashers
- Horn with turning signal lever

ENGINES	1000R
Type	101 hp / 69 lb-ft, Rotax 999 cc V-twin, DOHC, liquid cooled High flow radiator cooling fan of 120W & 500 cm <sup>3</sup>
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P
Drive Train	Selectable 4WD / 6WD / Lock 6WD with Visco-4Lok front differential
Driving assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched Double A-arm with sway bar 7.5 in. (19.5 cm) travel
Front Shocks	SHOWA Internal Floating Pistons (IFP) Shocks
Rear Suspension	Arched Double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel
Rear Shocks	SHOWA Internal Floating Pistons (IFP) Shocks

TIRES / WHEELS	
Front & Rear Tires	XPS Iron Force - 30 x 9 x 14 in.
Wheels	14 in. Aluminum beadlock

BRAKES	
Front	Oversized Dual 252 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

## DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,374 lb (623 kg)
L x W x H (includes mirrors)	119.1 x 50.2 x 58.1 in. (302.5 x 127.4 x 147.5 cm)
Wheelbase	85.7 in. (217.6 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	37.8 in. (96 cm)
Rack Capacity	Front: 120 lb (54.4 kg)
Storage Capacity	Front cargo: 8 gal (30 L) Rear cargo: 58 gal (220 L) Rear undercargo: 6.6 gal (25 L) Total: 72.6 gal (275 L)
Towing Capacity	1,830 lb (830 kg)
Bed Capacity	1000 lb (454 kg)
Fuel Capacity	5.1 gal (19.5 L)

## FEATURES

Gauge	7.6 in. wide digital display
Magneto	650-W
Instrumentation	Phone storage & USB-C charger
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and tail lights LED signature
Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable
Seat	Special Edition
Handlebar	Aluminium U type (57 mm)
Protection	Heavy Duty front bumper Full skid plate Footwell protectors Front & rear a-arms protectors Handguards
Hitch Type	2 in. Rear hitch and tow ball

## WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.